



APEX 7000



- Superior Blade, Tool and Wheel Life
- Excellent Lubricity
- Superior Tramp Oil Rejection
- Mild Pleasant Odor
- Excellent Corrosion Protection

PRODUCT DESCRIPTION

APEX 7000 is a moderate to heavy duty semi-synthetic water soluble cutting and grinding fluid. It is manufactured for turning, milling, drilling, sawing, and grinding in individual machine sumps or central systems. It will increase blade, tool, or wheel life and production. The raw materials are designed to resist bacteria and fungus. It provides long term worry free sump life. This product can be used on ferrous and nonferrous metals.

RECOMMENDED STARTING DILUTIONS

Operation	Carbon Steels, Cast Steels	High Alloy Steels, Stainless Steels	Aircraft, Tool Steels	Copper, Aluminum
Machining-Milling, Drilling, Turning	1:20 (5.0%)	1:15 (6.7%)	1:10 (10.0%)	1:20 (5.0%)
Grinding	1:25 (5.0%)	1:20 (5.0%)	1:20 (5.0%)	1:20 (5.0%)
Reaming, Tapping, Sawing, Broaching	1:15 (6.7%)	1:10 (10.0%)	1:10 (10.0%)	1:15 (6.7%)

REFRACTOMETER READINGS

Dilution Ratio	1:10	1:15	1:20	1:25	1:30
	(10.0%)	(6.7%)	(5.0%)	(4.0%)	(3.3%)
Refractometer Reading	4.9	3.4	2.6	2.1	1.7

TYPICAL ANALYSIS

FORM:	Liquid
COLOR:	Blue
SPECIFIC GRAVITY:	1.02
FLASH POINT:	None
ODOR:	Mild
pH @ 5% SOLUTION:	9.3

AVAILABILITY

A-4701-14 1 Gallon (4/Case) A-4705-05 5 Gallon Pail A-4755-55 55 Gallon Drum

Ashburn Chemical Technologies 7403 Wright Rd.

Houston, Texas 77041 Ph: (832) 399-1000 Fax: (832) 399-1010 www.ashburnchemical.com