

## **Technical Data Sheet**

# MIKE-O-DRILL DH-60



- Superior EP and Lubricity Additives
- Low Viscosity
- Excellent Chip Removal
- Improved Finish
- Excellent Blade and Tool Life

#### PRODUCT DESCRIPTION

MIKE-O-DRILL DH-60 is a heavy duty, light viscosity cutting oil. Sulfurized and chlorinated extreme pressure additives provide hydrodynamic and polar lubrication. This product is recommended for screw machines, chuckers, band saws, and bar machines. The MIKE-O-DRILL outperforms other cutting oils in deep hole drilling, heavy cutting, gundrilling, sawing, and other difficult operations. It is ideal for both ferrous and non ferrous materials. Staining may occur on copper if part is not rinsed soon after machining.

#### TYPICAL ANALYSIS

WEIGHT:	7.5 LB/ GL.
FLASH POINT:	>250° F (TCC Method)
VISCOSITY:	68 SSU @ 100° F
APPEARANCE:	Dark Oil, Light Viscosity, Slight Sulfur Odor

### AVAILABILITY

E-2253-14 1 Gallon (4/Case)

E-2254-05 5 Gallon E-2255-55 55 Gallon

**Ashburn Chemical Technologies** 

7403 Wright Rd.
Houston, Texas 77041
Ph: (832) 399-1000
Fax: (832) 399-1010
www.ashburnchemical.com