

# ENVIRO GREEN *extreme* SG

## Biodegradable Industrial Cleaner Degreaser Solvent

- Heavy Duty Cleaning and Degreasing
- Removes All Grease, Grime and Soil
- Excellent for Parts Washers

### REMOVES:

- Heavy Viscosity Oils
- Greases
- Cutting and Forming Oils
- Rust Preventative Films
- Oxidized and Gummy Deposits

### FOR:

- Metal Parts and Surfaces
- Engine Degreasing
- Industrial Equipment
- Machinery

### ■ PRODUCT INFORMATION

ENVIRO-GREEN EXTREME SG is a multi-purpose, heavy duty, natural bio-based solvent degreaser. It is biodegradable, non-toxic and VOC exempt. Removes heavy grease, oils and dirt quickly and safely. Use to degrease and clean automotive parts, oilfield equipment, machined parts, industrial machinery and other difficult-to-clean surfaces.

Replaces and outperforms d'limonene degreasers and petroleum solvents such as mineral spirits and naphtha.

### ■ APPLICATIONS

#### PARTS WASHING SOLVENT:

Excellent for replacing petroleum solvents in parts washing equipment. Safe, non-flammable alternative to mineral spirits and other petroleum products. Removes lubricants and cutting oils from machined parts. Provides short-term corrosion protection to prevent flash rust on parts. Use on Ferrous and Non-Ferrous Metals. Safe on most plastics.

Machined Parts ■ Engines ■ Transmissions ■ Rear Ends

#### HEAVY DUTY DEGREASING:

Removes all grease and oil from metal surfaces. Removes petroleum based oils as well as animal fats and vegetable based oils.

Grease ■ Motor Oil ■ Lubricants ■ Carbon Deposits ■ Cutting Fluids  
Animal Fats ■ Vegetable Oils

Machine Shops ■ Industrial Plants ■ Commercial Facilities

#### OTHER APPLICATIONS:

Removes Asphalt Residue ■ Removes Most Adhesives ■ Storage Tank Cleaning



Biodegradable Industrial Cleaner Degreaser Solvent

TYPICAL ANALYSIS

VOC:.....Exempt
EVAPORATION RATE: ..... < 0.01
KB VALUE: ..... 61 (d'Limonene KB: 56, Mineral Spirits KB: 35)
SPECIFIC GRAVITY: ..... 0.882 g/mL @ 25° C
APPEARANCE/ODOR: ..... Light Yellow Liquid/Slight Odor
DIELECTRIC STRENGTH: ..... 42.2 KV
BOILING POINT: ..... > 600° F
VAPOR PRESSURE: ..... < 1.0 mm Hg @ 68° F
HIGH FLASH POINT: ..... > 300° F (TCC Method)
READILY BIODEGRADABLE: .....95% degraded in soil in 28 days
SARA TITLE III 313 ..... Not Reportable
TSCA (Toxic Substance Control Act):..... Listed in Inventory

Table with 2 columns: Category and Rating. Rows: HEALTH (0), FLAMMABILITY (1), REACTIVITY (0), PERSONAL (A)



COMPARISONS with COMMON SOLVENTS

Table comparing EnviroGreen EXT SG with Mineral Spirits, VM&P Naphtha, Toluene, and d'Limonene across metrics: Flash Point, Boiling Point, Evaporation Rate, Specific Gravity, and Viscosity.

DIRECTIONS

This product is used straight and can be applied by dipping, brushing, or spraying. Its high flash point makes it safe for industrial applications.

AVAILABILITY

Table listing part numbers and sizes: M-02801 (1 Gal), M-02805 (5 Gal), M-02807 (55 Gal), M-02803 (275 Gal)



7403 Wright Rd.
Houston, Texas 77041
Ph: (832) 399-1000
Fax: (832) 399-1010
www.ashburnchemical.com