

METAL PARTS PROTECTOR

Aerosol

- Prevents Rust & Corrosion
- Weldable & Paintable
- Contains No Chlorinated or Fluorinated Solvents

WHERE

- Machine Shops ■ Factories
- Industrial Plants ■ Boats
- Manufacturing Plants ■ Ships
- Pipe Yards ■ Trucks & Cars
- Heavy Equipment
- Construction Vehicles

FOR

- Pipe Thread ■ Metal Parts
- Tools ■ Dies ■ Castings
- Pulleys ■ Hoists
- Riggings ■ Cables

Ashburn Chemical Technologies
7403 Wright Rd.
Houston, Texas 77041
Ph: (832) 399-1000
Fax: (832) 399-1010
www.ashburnchemical.com

■ PRODUCT DESCRIPTION

METAL PARTS PROTECTOR contains a flexible, weldable, metal parts protector. When applied, it will prevent rust and corrosion on all metal parts. Apply to machined parts, dies, pipe threads, casting, tools, jigs, and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings. Effective in protecting metal parts on boats, ships, and dock equipment. Affords long term protection for indoor or outdoor storage. Excellent for protecting materials while in transit.

■ DIRECTIONS

Product is most effective when parts are clean and free of rust, scale, or dirt. However, product will afford adequate protection when applied over these areas. Simply spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface. For extremely severe conditions, wait 5 minutes and apply another coat. Product will completely set in 2 hours. Once the film is hard, part can be handled. Dust and dirt can be wiped off without affecting film.



■ TYPICAL ANALYSIS

BOILING RANGE:	156+°F
COLOR:	Amber
DETERGENCY:	N/A
EVAPORATION RATE:	>1
FLASH POINT:	-142°F
FOAM STABILITY:	N/A
FRAGRANCE	Petroleum Solvent
FREEZE/THAW	3 Cycles
HARD WATER TOLERANCE	N/A
pH:	N/A
RINSEABILITY:	N/A
SHELF LIFE:	One Year +
SOAP CONTENT:	None
SOLUBILITY:	0%
SPECIFIC GRAVITY:	.76
VAPOR DENSITY:	>1
VAPOR PRESSURE:	24
VISCOSITY:	100 cts
% VOLATILE:	>76

■ AVAILABILITY

PART#	SIZE (QTY/CS)
M-25550	12.5 oz Aerosol