

# METAL PROTECTIVE COATING

- Superior Rust Prevention
- Excellent Salt Spray Protection
- Water Displacing
- Non-Greasy Film Residue
- Moderate Outdoor Protection

**WHERE**

- Industrial ■ Pipe Yards
- Construction ■ Automotive
- Manufacturing
- Machine Shops

**FOR**

- Metal Parts ■ Pipe
- Equipment ■ Machinery
- Tools ■ Steel Girders

**Ashburn Chemical Technologies**  
7403 Wright Rd.  
Houston, Texas 77041  
Ph: (832) 399-1000  
Fax: (832) 399-1010  
[www.ashburnchemical.com](http://www.ashburnchemical.com)

■ **PRODUCT DESCRIPTION**

A fast drying solvent based coating and rust preventative that dries to a tacky finish. May be easily removed with solvents. A ready to use product for use on pipes, metal parts, equipment and machinery. Excellent for short or long term storage and for protection of metallic surfaces.

■ **INSTRUCTIONS**

Apply product as is with either a brush or sprayer to all surfaces needing protection, paying particular attention to cracks and crevices. Allow to air dry. To increase protection and long term storage, repeat application. Product can be removed with solvent.

■ **PROTECTION**

Indoors ..... up to 2 years  
Outdoors ..... 12-18 months

■ **TYPICAL ANALYSIS**

BOILING RANGE:	105+°F
COLOR:	Dark Brown
DETERGENCY:	N/A
EVAPORATION RATE:	<1
FLASH POINT:	145°F
FOAM STABILITY:	N/A
FRAGRANCE	N/A
FREEZE/THAW	3 Cycles
HARD WATER TOLERANCE	N/A
pH:	N/A
RINSEABILITY:	N/A
SHelf LIFE:	One Year +
SOAP CONTENT:	None
SOLUBILITY:	Insoluble
SPECIFIC GRAVITY:	.84
VAPOR DENSITY:	>1
VAPOR PRESSURE:	10
VISCOSITY:	75 cts
% VOLATILE:	72

■ **AVAILABILITY**

PART#	SIZE (QTY/CS)
M-27111	1 Gallon
M-27115	5 Gallon
M-27117	55 Gallon