



# COOLANT CONDITIONER

### **Description:**

ASHBURN COOLANT CONDITIONER is a sumpside additive designed to eliminate foul odors associated with metalworking fluids. It is formulated for use in various applications as an additive for emulsions and aqueous systems where control of biomass is critical. It prolongs the useful life of metalworking fluid solutions and greatly reduces the costs associated with clogged filters, coolant removal, sump cleaning, machine tool downtime, and disposal of the spent metalworking fluid. It ensures the system will continue to function as it was designed, and reduces degradation and changes in physical properties. One pint of product will treat 100 gallons of diluted coolant.

### **Advantages:**

- ELIMINATE FOUL ODORS
- PROLONGS COOLANT LIFE
- BETTER OVERALL SHOP APPEARANCE
- REDUCES OVERALL COSTS OF PRODUCTION

### **Typical Analysis:**

Appearance: ..... Yellow to Amber Liquid  
Odor: ..... MILD  
PH: ..... 8.5 to 9.0  
Density (lb/gal): ..... 8.7  
Solubility in water: ..... Complete

### **RECOMMENDED APPLICATIONS:**

Please contact your Ashburn Chemical Technology sales representative for more detailed information before using this product.

### **Added Sumpside:**

For a non-fouled system use 4 to 8 ounces per 100 gallons of emulsion every 4 to 6 weeks. For a noticeably fouled system use an initial dose of 12 to 16 ounces per 100 gallons of emulsion followed by subsequent maintenance doses.

### **Availability:**

B-4160-16     16oz. Bottles (12/case)  
B-4160-14     1 Gallon Jugs (4/case)  
B-4160-05     5 Gallon Pail