

Deep Draw

Features & Benefits

- Superior EP & Lubricity Additives
- Good Rust Protection
- Stable Emulsion
- Reduced Frictional Wear & Welding
- Improved Finish
- Excellent Die Life

PRODUCT DESCRIPTION

Ashburn Deep Draw is a heavy-duty, water soluble drawing compound designed to be used in a wide range of applications and severities. It will perform on both ferrous and nonferrous materials. Due to the quality of raw materials, this product can handle a tremendous range of drawing and stamping applications.

APPLICATION

Ashburn Deep Draw can be used straight, or depending on the severity of the application, diluted as much as 10:1 with water.

TYPICAL ANALYSIS

APPEARANCE: Dark Oil
 WEIGHT: 8.5 LB/GL
 FLASH POINT: >300°F (TCC METHOD)
 SULFUR: NONE
 CHLORINE: <7%
 PHOSPHOROUS: NONE

PACKAGING

E-2463-14 1 Gallon (4/case)
 E-2464-05 5 Gallon
 E-2465-55 55 Gallon

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com

