

DS 2470

Features & Benefits

- Medium Viscosity
- Superior EP & Lubricity Additives
- Good Rust Protection
- Improves Finish
- Excellent Die Life
- Reduces Frictional Wear & Welding
- Residual Coating can be Welded Through
- Does Not Contain Phosphorous

PRODUCT DESCRIPTION

Ashburn DS 2470 is an extremely heavy duty drawing and stamping oil designed to be used in a wide range of applications and severities. It will perform on both ferrous and nonferrous materials. This product has excellent adherence and anti-wipe properties.

APPLICATION

Ashburn DS 2470 can be used straight, or depending on the severity of the application, diluted with a solvent such as mineral spirits. The product can be applied by brushing, dipping, spraying, rolling, or other convenient methods.

TYPICAL ANALYSIS

APPEARANCE: Amber Oil
 WEIGHT: 8.0 LB/GL
 FLASH POINT: > 335°F (COC METHOD)
 VISCOSITY: 275 SUS @ 100°F
 SULFUR: ,5%
 CHLORINE: <10%
 PHOSPHOROUS: NONE

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.

PACKAGING

E-2470-05 5 Gallon
 E-2470-55 55 Gallon



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com

