

DS 6000 PLUS

Features & Benefits

- Excellent Boundary Lubrication
- Superior Rust and Corrosion Protection. Protects Both Ferrous and Non-Ferrous Metals
- Prevents Bimetallic Corrosion And is Safe to Use in Equipment with Copper, Brass, Bronze, and Aluminium Components
- Chlorine-Free, Sulfur Free

Synthetic Drawing & Stamping Fluid

PRODUCT DESCRIPTION

Ashburn DS 6000 PLUS is a synthetic drawing and stamping fluid designed to be used in a wide range of applications and severities. Provides excellent extreme pressure lubricity without the use of chlorinated or sulfurized additives. It will perform on both ferrous and nonferrous materials. Recommended for drawing, stamping, punching, bending, and forming.

RECOMMENDED STARTING DILUTION

Ashburn DS 6000 PLUS can be used straight, or depending on the severity of the application, diluted as much as 50:1 with water. The product can be applied by flooding, immersion, spraying, brushing or roll coating.

TYPICAL ANALYSIS

FORM:Liquid
 COLOR: Blue or Undyed
 SPECIFIC GRAVITY: 1.04
 FLASH POINT:None
 ODOR:..... Mild
 pH @ 5% conc: 9.0

PACKAGING

BLUE

E-2660-05 5 Gal Pail
 E-2660-55 55 Gal Drum
 E-2660-275 275 Gal Tote

UNDYED

E-2661-05 5 Gal Pail
 E-2661-55 55 Gal Drum
 E-2661-275 275 Gal Tote



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com