

# Vanishing Oil ML

## Features & Benefits

- No Oily Residue
- Non-Reactive to Metals
- Ideal for Drawing & Stamping  
(light gauge material)
- Works on Ferrous &  
Nonferrous Metals
- Excellent Lubrication

## PRODUCT DESCRIPTION

**Ashburn Vanishing Oil ML** is a very low viscosity oil which is fortified with mild extreme pressure additives. It will evaporate at room temperature in a few hours after use. This product leaves an excellent finish on cut, drawn or stamped parts.

## APPLICATION

**Ashburn Vanishing Oil ML** is ready to use, do not dilute.

## TYPICAL ANALYSIS

APPEARANCE: ..... Clear Oil  
 DENSITY: ..... 7.4 LB/GL  
 FLASH POINT: ..... > 266°F (PMCC METHOD)  
 SOLUBILITY IN WATER: ..... Nil  
 VISCOSITY: ..... 43 SSU @ 100°F  
 SULFUR: ..... NONE  
 CHLORINE: ..... <5.00%  
 PHOSPHOROUS: ..... NONE

## PACKAGING

E-7521-14	1 Gallon (4/case)
E-7522-05	5 Gallon
E-7523-55	55 Gallon
E-7523-275	275 Gallon

## NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.



7403 Wright Rd. Houston, TX 77041  
 ph: 832.399.1000 fax: 832.399.1010  
 www.ashburnchemical.com

