

# Penetrating Lube Aerosol

## Features & Benefits

- Reduces Friction & Retards Wear
- Temperature Range: -110°F to +1050°F
- Contains Molybdenum Disulfide & Graphite
- Does Not Carbonize

## Where

- Manufacturing • Oil Rigs
- Industrial Machinery
- Airplanes • Machine Shops
- Homes, Hotels & Motels
- Cars & Trucks

## For

- Machine Parts • Door Hinges
- Motors • Nuts & Bolts
- Locks • Wire Cable
- Refrigeration Equipment
- Ignition Systems

## PRODUCT DESCRIPTION

**PENETRATING LUBE** is a lubricating product formulated to quickly penetrate rust, corrosion and moisture. Lubricates, cleans and contains rust preventatives. Non-flammable and nonconductive to 30,000 volts. Four way action cleans, lubricates, prevents rust and penetrates.

## APPLICATION

Shake well before using. Hold can eight to ten inches from surface to be treated. Spray liberally directly on area to be treated. Product will penetrate immediately. Reapply periodically as required.

## TYPICAL ANALYSIS

APPEARANCE:.....Clear  
 SPECIFIC GRAVITY:..... .98  
 DETERGENCY:..... N/A  
 EVAPORATION RATE:..... > 1  
 FRAGRANCE:.....Chlorinated Solvent  
 FREEZE/THAW:..... 3 Cycles  
 SHELF LIFE: ..... One Year +  
 % VOLATILE: ..... > 95  
 VAPOR DENSITY:..... > 1  
 VAPOR PRESSURE: ..... 15  
 pH:..... N/A  
 BOILING RANGE: ..... 250° F  
 HARD WATER TOLERANCE:..... N/A  
 VISCOSITY:..... 100 CTS  
 SOLUBILITY:.....0%  
 SOAP CONTENT:.....None  
 FOAM STABILITY:..... N/A  
 FLASH POINT: .....None  
 RINSABILITY:..... N/A

## PACKAGING

M-25500 18 Oz. (12/Case)



7403 Wright Rd. Houston, TX 77041  
 ph: 832.399.1000 fax: 832.399.1010  
 www.ashburnchemical.com

