

Cleaner Degreaser Non-Flammable

Features & Benefits

- Non-Conductive
- Leaves No Residue
- Dielectric Strength to 29,000 Volts
- Contains No Oil

Where

- Industrial Plants
- Machine Shops
- Institutions

For

- Gas Engines
- Machinery
- Equipment
- Services
- Electric Motors
- Electrical Parts

PACKAGING

M-05131	1 Gal (4/Case)
M-05135	5 Gal Pail
M-05137	55 Gal Drum

PRODUCT DESCRIPTION

This product is a highly concentrated solvent designed to remove dirt, grease, oil and grime from metallic and non-metallic surfaces. Cleaning is quick and simple without the danger of injury to working parts. Ideally suited for use on electric motors even while running, electronic equipment, ignition systems, generators, power tools, etc. Also use on air conditioning, refrigeration and all types of mechanical equipment. NOTE: Do not use on automatic electronic process control or monitoring systems, computers or data processing equipment. May affect certain plastics. Test before using.

APPLICATION

This product is used straight and can be applied by dipping, brushing or spraying. When spraying, allow the solvent to set for a minute, then wipe or rinse off with a second spray. On heavily encrusted areas use a brush. Product is non-flammable and non-conductive so it can be used while motors and equipment are operating.

TYPICAL ANALYSIS

APPEARANCE:	Clear
SPECIFIC GRAVITY:	1.46
FLASH POINT:	None
DETERGENCY:	N/A
EVAPORATION RATE:	> 1
FRAGRANCE:	Chlorinated
SOLIDS:	0%
SHELF LIFE:	One Year +
% VOLATILE:	99 +
VAPOR DENSITY:	4.53
VAPOR PRESSURE:	.60 mmHg
pH (concentrate):	N/A
BOILING RANGE:	189° F
FOAM STABILITY:	N/A
FREEZE/THAW:	3 Cycles
VISCOSITY:	0 CTS
SOLUBILITY:	Nil
SOAP CONTENT:	None
RINSABILITY:	Excellent
HARD WATER TOLERANCE:	N/A



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com

