

Ashburn Cutting Oil

Features & Benefits

- Superior EP and Lubricity Additives
- Excellent for Use on Non-Ferrous Metals
- Does Not Contain Chlorine or Sulphur
- Low Viscosity
- Provides Excellent Finish
- Extends Tool and Wheel Life

AL-60

PRODUCT DESCRIPTION

A premium quality, transparent, heavy duty cutting oil formulated with highly refined base stocks. Specially formulated for use on non-ferrous metals including aluminum, copper and brass. This product offers excellent anti-weld properties and forms effective boundary lubrication which reduces heat and extends tool life. The additive system also provides anti-misting properties along with good surface finish on the work piece.

APPLICATION

Excellent for use in turning, milling, drilling, grinding and in screw machines and threading applications on all non-ferrous metals.

TYPICAL ANALYSIS

Appearance	Transparent, Yellow liquid
Odor.....	Mild
Solubility in Water.....	Insoluble
Flash Point	> 300°F
Specific Gravity.....	0.88
Viscosity	58 SUS @ 100°F
Evaporation Rate (Butyl Acetate =1)	<1.0

PACKAGING

E-3760-05	5 Gal Pail
E-3760-55	55 Gal Drum
E-3760-275	275 Gal Tote



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com