

APW-80

Features & Benefits

- Heavy Duty Hot Tank Cleaner
- Removes Grease, Grime and Carbon
- Concentrated

PRODUCT DESCRIPTION

A highly alkaline, hot tank cleaner formulated to remove grease, oil, dirt, carbon, and light rust from metal surfaces. Recommended for use in plant maintenance shops, equipment overhaulers and engine rebuilders.

DIRECTIONS

The usage and concentration can vary depending on the job. Normal dilution ratio is 8:1 (8 parts water to 1 part product)

TYPICAL ANALYSIS

BOILING POINT:	212°F
COLOR:	Yellow
DETERGENCY:	Excellent
EVAPORATION RATE (butyl acetate = 1):	<1
FLASH POINT:	N/A
FOAM STABILITY:	Excellent
FRAGRANCE:	None
FREEZE/THAW:	3 Cycles
HARD WATER TOLERANCE:	Excellent
pH at 33% Conc:	14.5
RINSEABILITY:	Excellent
SHELF LIFE:	One Year +
SOAP CONTENT:	None
SOLUBILITY:	100%
SPECIFIC GRAVITY:	1.4
VAPOR DENSITY (Air=1):	>1.0
VAPOR PRESSURE@68°F:	>1.0

CAUTION

Contains Potassium Hydroxide. Use only in well ventilated area. Operators should always wear goggles, rubber gloves, apron and boots. Avoid contact with eyes or prolonged contact with skin. In case of contact, flush freely with water. If swallowed, give water, call physician.

PACKAGING

H-7328-14	1 Gallon (4/case)
H-7328-05	5 Gallon
H-7328-55	55 Gallon
H-7328-275	275 Gallon



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com