

# Clear Coat 33

## PRODUCT DESCRIPTION

**CLEAR COAT 33** is water-soluble rust and corrosion preventative designed for protection of ferrous and nonferrous materials. This product will provide up to 6 months of rust protection. Leaves a solid, clear, non-tacky coating. Does not leave fingerprints.

## APPLICATION

**CLEAR COAT 33** should be used straight (undiluted)  
Can be applied by brushing, dipping, spraying, or flooding.

NOTE: Dry times for coating will vary with conditions.

Normal Dry Time ..... 20 minutes min.

Heat 100 - 110° F ..... 15 minutes min.

High Humidity..... 40 minutes min.

For best results, allow 60 minutes drying time.

Once the film is hard, part can be handled.

Dust and dirt can be wiped off without affecting film.

Fingerprint free once dried.

## TYPICAL ANALYSIS

APPEARANCE:..... Tan Opaque Liquid  
ODOR:..... Mild, Waxy Odor  
SPECIFIC GRAVITY:.....1.0  
pH:.....8.0  
RESIDUE:.....Solid Clear Coating

## PACKAGING

L-3300-14      1 Gallon (4/case)  
L-3300-05      5 Gal Pail  
L-3300-55      55 Gal Drum  
L-3300-275    275 Gal Tote



7403 Wright Rd. Houston, TX 77041  
ph: 832.399.1000 fax: 832.399.1010  
www.ashburnchemical.com