

R&O Hydraulic Oil 32

Features & Benefits

- Protects Against Oxidation, Rust and Corrosion
- Low Foaming
- Non-Detergent

PRODUCT DESCRIPTION

Ashburn R & O Hydraulic Oil is blended from highly-refined base stocks to provide outstanding lubricating properties in a wide-range of applications. It is formulated with select additives to provide excellent anti-rust, anti-oxidation, anti-corrosion and anti-foam performance.

APPLICATIONS

- Non-Critical hydraulic applications
- Low pressure circulating fluid
- Air-tool oil
- General machine oil
- Drip or splash lubricant
- Spindle Oil
- Lubrication of light-duty compressors

TYPICAL ANALYSIS

SPECIFIC GRAVITY:.....	0.894
GRAVITY, API 60 °F:	26.0
FLASH POINT COC (°F):	390+
VISCOSITY, cSt at 40 °C:.....	30 - 42
VISCOSITY, SUS at 100 °F:.....	150
POUR POINT (°F):	-10
Approx. SAE:.....	10
ISO VG NUMBER:.....	32

PACKAGING

F-8020-14	1 Gallon
F-8020-05	5 Gallon Pail
F-8020-55	55 Gallon Drum
F-8020-275	275 Gallon Tote



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com