

Gear Oil EP460

Features & Benefits

- Superior Lubrication & EP Characteristics
- Excellent Thermal Stability
- Protects Against Rust & Corrosion

PRODUCT DESCRIPTION

Ashburn Gear Oil EP460 is a heavy duty, premium gear oil fortified with extreme pressure (EP) additives for the lubrication of enclosed gear drives.

It is thermally stable, resists sludge formation and is chemically stable. It separates quickly from water and will not contribute to the formation of metal-etching acids or corrosives. Protects against rust and corrosion.

APPLICATIONS

Recommended for use in moderate to severe conditions in applications where the equipment manufacturer specifies an AGMA EP gear oil.

For use in gear drives including planetary, spur, bevel, helical, herringbone and worm gearing. Also for use in non-gear applications including heavily loaded plain and rolling contact bearings operating at slow speeds.

TYPICAL ANALYSIS

ISO VG NUMBER:.....	460
AGMA Grade	7 EP
SPECIFIC GRAVITY	0.9
POUNDS PER GALLON:	7.5
FLASH POINT (°F):	480
VISCOSITY, CST at 40 C:	460
VISCOSITY, SUS at 100 F:	2466
POUR POINT (°F):	0

PACKAGING

F-9012-05	5 GALLON
F-9012-55	55 GALLON
F-9012-275	275 GALLON



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com