

# RPL #5



## FEATURES & BENEFITS

- Long-term indoor humidity protection
- Salt spray protection
- Water displacing
- Ease of removal
- Oily lubricating film
- Protects ferrous and non-ferrous metals

## RUST PREVENTATIVE

### PRODUCT DESCRIPTION

**RPL #5 RUST PREVENTATIVE** is a water displacing, non-staining rust preventive and lubricant that provides an oily protective film for 18 to 24 months indoor storage protection, moderate salt spray protection and short term outdoor protection.

RPL #5 can be applied by spraying, brushing, dipping or submersion. The thin oily film suppresses fingerprints and is easily removed by wiping or cleaning with solvent or alkaline cleaners.

### PROTECTION

Indoors ..... 18 to 24 months

Outdoors ..... short term

### TYPICAL ANALYSIS

APPEARANCE: ..... Amber Fluid

DENSITY: ..... 7.01 LB/GL

SPECIFIC GRAVITY: ..... 0.84 @ 60° C

VISCOSITY: ..... 42 SUS @ 100° F

FLASH POINT: ..... 170°F (Method: ASTM D3278, Closed Cup)

FILM TYPE: ..... Soft, Oily

## PACKAGING

L-2515-14	1 Gallon (4/case)
L-2515-05	5 Gal Pail
L-2515-55	55 Gal Drum