

# **Safety Data Sheet**

Issue Date: 16-Jul-2015 Review Date: 03-Mar-2021 Version 1

# 1. IDENTIFICATION

Product Identifier

Product Name ONE SHOT PENETRATING OIL (AEROSOL)

Other means of identification

SDS#

ITEM# M-25340

**UN/ID No** UN 1950

Recommended use of the chemical and restrictions on use

Recommended Use Penetrating Lubricant

Details of the supplier of the safety data sheet

**Supplier Address** 

Ashburn Chemical Technologies

7403 Wright Rd Houston, TX 77041

**Emergency Telephone Number** 

Company Phone Number Emergency Telephone (24 hr) 832-399-1000

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

Appearance Brown spray Physical State Aerosol Odor Petroleum-solvent like

#### Classification

Flammable Aerosol (liquefied gas)	Category 1
Eye irritant	Category 2B
Aspiration Hazard	Category 1

# Hazard Not Otherwise Classified (HNOC): N/A

Signal Word DANGER



# **Hazard Statements**

Extremely flammable aerosol
Contains gas under pressure: May explode if heated
Causes skin and eye irritation
May be fatal if swallowed and enters airways

#### **Precautionary Statements - Prevention**

#### **Revision Date:**

Wash hands thoroughly after handling.

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use.

#### <u>Precautionary Statements - Response</u>

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store lock up. Do not expose/stare to temperatures exceeding 50°C/122°F. Store in a well-ventilated place

#### **Precautionary Statements - Disposal**

Dispose of contents and container in accordance with local, state, and national regulations.

#### **Unknown Acute Toxicity**

About 0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Isoparaffinic Hydrocarbon	64742-47-8	15-40
Mineral Seal Oil	64741-44-2	15-40
Petroleum Distillate, Solvent-Refined Heavy Paraffinic	64741-88-4	5-10
Petroleum Distillate, Solvent-Refined Light Paraffinic	64741-89-5	1-5
Mineral Spirits	64475-85-0	1-5
Ethyl Acetate	141-78-6	3-7
Propane / n-Butane	68476-86-8	10-30

<sup>\*\*</sup>If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

# 4. FIRST-AID MEASURES

#### First Aid Measures

**General Advice** Provide this SDS to medical personnel for treatment.

**Eye Contact** Rinse immediately with water for 15-20 minutes. If eye irritation persists: Get medical

advice or attention

Skin Contact Wash contact areas with soap and water for 15 minutes. Remove contaminated clothing

and shoes immediately. If skin irritation persists, call a physician.

**Inhalation** Remove person to fresh air and keep comfortable for breathing. Call a

poison center or doctor if you feel unwell

**Ingestion** Do not induce vomiting without medical advice. Seek immediate medical attention/advice.

## Most important symptoms and effects

Acute Health Hazard Eyes: redness, tearing, blurred vision

Skin: Prolonged or repeated contact may dry skin

Oral: Aspiration risk.

Chronic Health Hazard None known

Notes to Physician If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

Treat symptomatically.

#### **Revision Date:**

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

**Unsuitable Extinguishing Media** Do not use straight streams.

**Specific Hazards Arising from the Chemical** 

Contents under pressure. Exposure to temperatures above 120°F may cause bursting.

Hazardous Combustion Products Oxides of carbon

## Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** See Section 8 for Personal Protective Equipment.

**Environmental Precautions** See Section 12 for additional Ecological Information.

**Methods for Clean-Up** Use absorbent on spill sweep to clean. Dispose in accordance with local, state and federal

laws. Small releases may be wiped up with wiping material.

**Waste Disposal** Dispose of in accordance with local, State and Federal regulations. Do not dump in

> sewers. Use sand or other non-combustible absorbent material to clean up spill and place in container for later disposal. Containers may contain hazardous residue.

**RCRA Status** Waste solvent likely considered F003, Flammable, Non-halogenated solvent under

RCRA, however product should be fully, characterized prior to disposal (40 CFR 261)

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wash face, hands,

and any exposed skin thoroughly after handling.

Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product.

# Conditions for safe storage, including any incompatibilities

**Storage Conditions** Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not

expose to temperatures exceeding 50°C/122°F. Store locked up.

**Incompatible Materials** Strong oxidizing agents. Strong reducing agents.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isoparaffinic Hydrocarbon	5 mg/m3	5 mg/m3	
Mineral Seal Oil	5 mg/m3	5 mg/m3	

#### ONE SHOT PENETRATING OIL, Aerosol

#### **Revision Date:**

Petroleum Distillate, Solvent-Refined Heavy Paraffinic	Not Established	Not Established	
Petroleum Distillate, Solvent-Refined Light Paraffinic	Not Established	Not Established	
Mineral Spirits	300 ppm	500 ppm	-
Ethyl Acetate	400 ppm	400 ppm	-
Propane / n-Butane	1000 ppm	1000 ppm	-

#### Appropriate engineering controls

Engineering Controls General ventilation adequate

#### Individual protection measures, such as personal protective equipment

Personal Protective Equipment Safety glasses

**Respiratory Protection** Not required with adequate ventilation.

General Hygiene Considerations Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State Aerosol

Appearance Spray Odor Chlorinated solvent-like

ColorBrownOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting Point

Not determined

Boiling Point

> 180 °F / 82 °C

Freezing Point Not determined

Flammability Extremely flammable aerosol

Flash Point > 110 °F / 43 °C
Auto-ignition Temperature Not determined
Upper / Lower Flammability Limit Not determined

Vapor Pressure (mm Hg)30mm HgVapor Density1(Air = 1)

Evaporation Rate < 1 (butyl acetate = 1)

Specific Gravity 0.83 @ 77°F / 25°C

**pH** Not determined

Solids 0% Water Solubility 0%

Solubility in other solvents Not determined

Partition Coefficient Not determined n-Octanol/Water (Kow)

Volatility Including Water 22% Volatile

VOC Content (%) 21%

Dielectric Strength (Volts)

Decomposition Temperature

VIscosity

Not determined

Not determined

Not determined

# 10. STABILITY AND REACTIVITY

**Reactivity** Chemically active metals and bases.

<u>Chemical Stability</u> Stable under recommended storage conditions.

<u>Possibility of Hazardous Reactions</u> None under normal processing.

ONE SHOT PENETRATING OIL, Aerosol

**Revision Date:** 

**Conditions to Avoid** Temperatures greater than 122°F and source of ignition.

Incompatible Materials Strong acids, strong oxidizing agents.

<u>Hazardous Decomposition Products</u> Oxides of carbon, chlorine.

#### 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Eye Contact** May causes severe irritation, redness.

**Skin Contact** May cause irritation, localized defatting, dermatitis, with prolonged or repeated contact.

Inhalation May cause irritation to the respiratory tract, dizziness, headaches, drowsiness,

unconsciousness.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, vomiting, abdominal cramps.

#### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isoparaffinic Hydrocarbon (64742-47-8)	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	5000 mg/kg (Rat) 8 hr
Ethyl Acetate (141-78-6)	5620 mg/kg (Rat)	4935 mg/kg (Rabbit)	5 mg/L (Rat) 4 hr
Propane/n-Butane (68476-86-8)	-	-	685 mg/m <sup>3</sup> ( Rat) 4 hr

#### Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

# 12. ECOLOGICAL INFORMATION

**Isoparaffinic Hydrocarbon** (64742-47-8) **Ecotoxicity** 

Not expected to be harmful or demonstrate chronic toxicity toward aquatic organism.

**Ethyl Acetate** (141-78-6)

LC50 (Fatthead Minnow, 96hr) 220 mg/L; (Indian Catfish, 96hrs) 212.5 ppm

Persistence/Degradability Component(s) of this product are not biogradable.

Bioaccumulation This product is not expected to bioaccumulate.

This product is mobile in soil. Mobility

**Other Ecological Hazard** This material is toxic to aqua life.

# 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes** Dispose of in accordance with federal, state, and local regulations. Do not dump

in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or

reuse container.

#### **Revision Date:**

**RCA Status** Waste solvent likely considered F003, Flammable, Non-halogenated solvent under

RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

# 14. TRANSPORT INFORMATION

DOT

UN/ID No UN1950

**Proper Shipping Name** Aerosols, Ltd. Qty

Hazard Class / Division 2.1

Air shipment

UN/ID No UN1950

**Proper Shipping Name** Aerosols, Ltd. Qty

Hazard Class / Division 2.1

IMO/IMDG

**UN/ID No** UN1950

Aerosols, Ltd. Qty

**Proper Shipping Name** Hazard Class / Division 2.1 **Environmental Hazard Water** N/A

# 15. REGULATORY INFORMATION

International Regulations None-known

US Federal Regulations

**TSA STATUS** All Chemicals are listed or exempt.

**CERCLA** Ethyl Acetate (141-78-6) Reportable Quantity = 5,000 lbs

SARA 311/312 Hazard Categories Fire Health

**SARA 313 Reportable Ingredients** None

California Prop 65 This product contains no known chemicals regulated by Califonia's proposition 65.

# **16. OTHER INFORMATION**

**Health Hazards** Instability **Special Hazards** NFPA **Flammability** Not determined

**Personal Protection** HMIS **Health Hazards Flammability Physical Hazards** 

Issue Date: 16-Jul-2015

**Revision Date:** 

**Revision Note:** New format

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**