Technical Data Sheet



Features & Benefits

- Heavy Duty Cleaning • and Degreasing
- Removes All Grease. Grime and Soil
- **Excellent for Parts Washers**
- Non-Foaming
- Phenol Free
- Contains Corrosion Inhibitors

Removes:

- Heavy Viscosity Oils
- Greases
- Cutting and Forming Oils
- **Rust Preventative Films**
- Oxidized and Gummy Deposits

For:

- Metal Parts and Surfaces
- **Engine Degreasing** •
- Transmission Rebuilders
- Industrial Equipment
- Machinery





Extreme

Heavy Duty Concentrated **Cleaner Degreaser**

PRODUCT DESCRIPTION

ENVIRO-GREEN EXTREME is a heavy duty cleaner and degreaser designed to remove the most difficult soils. Removes oxidized and gummy deposits and accumulated soils. Cuts through any grease, dirt, soil, or grime and then suspends the soil.

Ashburn ion-Z Surfactant Technology utilizes a unique combination of cationic and nonionic surfactants that work together to quickly penetrate, detach and lift soils and greases to leave surfaces clean and residue free.

Excellent for use in automatic parts washers and pressure washing but also works well in immersion cleaning operations. Contains corrosion inhibitors to provide in-process rust protection.

APPLICATIONS

PARTS WASHING:

Excellent for replacing petroleum solvents in parts washing equipment. Safe, non-flammable alternative to mineral spirits and other petroleum products. Removes lubricants and cutting oils from machined parts. Provides short-term corrosion protection to prevent flash rust on parts.

Use on Ferrous and Non-Ferrous Metals. Safe on most plastics.

Machined Parts
Engines
Transmissions
Rear Ends

HEAVY DUTY DEGREASING:

in

Removes all grease and oil from metal surfaces. Removes petroleum based oils as well as animal fats and vegetable based oils.

Grease Motor Oil Lubricants Carbon Deposits Cutting Fluids Animal Fats
Vegetable Oils

Machine Shops
Industrial Plants
Commercial Facilities







EnviroGreen Extreme

Heavy Duty Concentrated Cleaner Degreaser

TYPICAL ANALYSIS

BOILING RANGE:	212+
COLOR:	Clear, light amber
EVAPORATION RATE:	< 1
FLASH POINT:	N/A
FOAM STABILITY:	Low Foam
ODOR:	Pleasant
FREEZE/THAW:	3 Cycles
HARD WATER TOLERANCE:	Excellent
pH (concentrate):	10.0-11.0
RINSEABILITY:	Excellent
SHELF LIFE:	
SOLUBILITY:	
SPECIFIC GRAVITY:	
VAPOR DENSITY:	>1
VAPOR PRESSURE:	

DIRECTIONS

HEAVY DUTY CLEANING: Dilute product from 1: 5 to 1:10 with water depending upon the soil conditions. For heavy soil, apply solution to the surface and allow to stand for 5 minutes to loosen soil. Rinse with water.

SPRAY WASHERS / AUTO PARTS WASHERS: Dilute product from 1:10 up to 1:30 depending on the severity of the application.

GENERAL CLEANING: Dilute product up to 1:50 with water. Spray, brush, or wipe solution onto surface to be cleaned. Wipe up solution with clean cloth or towel.

AVAILABILITY

PART#SIZE (QTY/CS)M-027011 Gal (4)M-027055 GalM-0270755 GalM-02703275 Gal





7403 Wright Rd. Houston, TX 77041 ph: 832.399.1000 fax: 832.399.1010 www.ashburnchemical.com

