

DS 2400

Features & Benefits

- Light Viscosity
- Superior EP & Lubricity Additives
- Good Rust Protection
- Improves Finish
- Increases Die Life
- Reduces Frictional Wear
& Welding

PRODUCT DESCRIPTION

Ashburn DS 2400 is a drawing oil fortified with extreme pressure additives. It is designed to be used in a wide range of applications and severities. It's light viscosity allows it to flow easily. It will perform on both ferrous and nonferrous materials. This product can handle a tremendous range of applications including deep drawing, stamping, punching, bending and forming.

APPLICATION

Ashburn DS 2400 should be used undiluted. The product can be applied by flooding, immersion, spraying, brushing or roll coating.

TYPICAL ANALYSIS

APPEARANCE: Amber Oil
 WEIGHT: 7.8 LB/GL
 FLASH POINT: > 142°F (TCC METHOD)
 ODOR: Slight Solvent
 VISCOSITY: 70 SUS @ 100°F
 SULFUR: NONE
 CHLORINE: <15%
 PHOSPHOROUS: NONE

PACKAGING

E-2400-05 5 Gallon
 E-2400-55 55 Gallon

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com

