



Heavy Duty

Cleaner Degreaser Concentrate

Features & Benefits

- Removes Baked-On Carbon Deposits
- Deep Cleaning Formula
- Rapidly Removes Grease and Oil
- Does Not Emulsify Oil – Rejects Oil to the Surface
- Safe, Water-Based Formula
- Weldable and Paintable
- Contains Corrosion Inhibitors
- Produces Cleaner & Brighter Parts

Removes:

- Baked-On Carbon Deposits
- Heavy Viscosity Oils
- Greases
- Waxes
- Oxidized and Gummy Deposits

For:

- Metal Parts and Surfaces
- Industrial Equipment
- Machined Parts
- Engine Remanufacturing
- Transmission Remanufacturing

PRODUCT DESCRIPTION

ENVIROGREEN CARBX HD is a powerful, heavy-duty cleaner and degreaser formulated to remove the most difficult soils including baked-on carbon deposits. Excellent for use in ultrasonic and immersion cleaning of ferrous and non-ferrous parts. Formulated to cut through any grease, dirt, oil, and grime and then suspend the soil. Surfaces will be residue free and can be welded or painted. Contains corrosion inhibitors to provide in-process rust protection.

APPLICATIONS

IMMERSION CLEANING:

Safe, non-flammable replacement for petroleum solvents.
 Can be used on all ferrous and non-ferrous materials including aluminum.*
 Use to remove carbon deposits and degrease and clean

Remanufactured components ■ Engines ■ Transmissions
 Machined parts ■ Industrial parts

* For aluminum, mix concentration must be at or below 10%. Material compatibility should always be confirmed.

HEAVY DUTY DEGREASING:

Excellent degreaser for use in removing grease and oil from metal surfaces.
 Removes petroleum based oils as well as animal fats and vegetable based oils.

Grease ■ Motor Oil ■ Lubricants ■ Carbon Deposits ■ Cutting Fluids
 Animal Fats ■ Vegetable Oils

Machine Shops ■ Industrial Plants ■ Commercial Facilities



Heavy Duty Cleaner Degreaser Concentrate

TYPICAL ANALYSIS

BOILING RANGE:	212+
COLOR:	Clear, light Yellow
EVAPORATION RATE:	< 1
FLASH POINT:	N/A
FOAM STABILITY:	Low Foam
ODOR:	Mild
FREEZE/THAW:	3 Cycles
HARD WATER TOLERANCE:	Excellent
pH (concentrate):	14.0
RINSEABILITY:	Excellent
SHELF LIFE:	One Year +
SOLUBILITY:	100%
SPECIFIC GRAVITY:	1.2

DIRECTIONS

IMMERSION CLEANING: Dilute product from 3% to 10% with water depending upon the soil conditions. Fill tank to level as recommended by the equipment manufacturer. Optimal temperature range: 130° F to 180° F

HEAVY DUTY DEGREASING: Dilute product from 3% to 10% with water depending upon the soil conditions. Spray, brush, or wipe solution onto surface to be cleaned. Wipe up solution with clean cloth or towel.

AVAILABILITY

PART#	SIZE (QTY/CS)
M-02865	5 Gal
M-02867	55 Gal
M-02863	275 Gal



7403 Wright Rd. Houston, TX 77041
ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com