## **PCR 40**

#### **Features & Benefits**

- Removes Grease, Oil,
  Carbon, Paint and Gaskets
- For High Temperature
  Operations 160°F to 180°F
- Non-Flammable

# Powder Coating and Gasket Remover

#### PRODUCT DESCRIPTION

**PCR 40** is a powerful, heavy-duty cleaner, degreaser, paint and gasket remover specially developed for high-temperature operations from 160°F to 180°F.

Use to clean and remove powder coating, paint, gaskets and carbon from automotive parts, oilfield equipment, machined parts, industrial machinery and other difficult-to-clean surfaces.

Excellent for use in hot tank immersion cleaning operations.

#### TYPICAL PROPERTIES

APPEARANCE:	Clear Yellow Liquid
ODOR:	Mild
SPECIFIC GRAVITY:	1.08
pH:	2.8-3.2
FLASH POINT:	None
SOLUBILITY IN WATER:	Completely Soluble

### **DIRECTIONS**

#### Heavy Duty Cleaning and Paint/Gasket Removal

Add one gallon of concentrate per 3 gallons of water to make a 25% dilution. Tank should be heated to a temperature between 160°F and 180°F. Immerse parts into tank and soak for 20 to 45 minutes depending on the application.

### **PACKAGING**

M-02885 5 Gal Pail M-02887 55 Gal Drum M-02883 275 Gal Tote















