



ENVIROGREEN EXTREME SG

BIODEGRADABLE INDUSTRIAL CLEANER DEGREASER SOLVENT

FEATURES AND BENEFITS

- Heavy duty cleaning and degreasing
- Removes all grease, grime and soil
- Excellent for parts washers
- NSF K1 Registered

REMOVES:

- Heavy viscosity oils
- Greases
- Cutting and forming oils
- Rust preventative films
- Oxidized and gummy deposits

FOR:

- Metal parts and surfaces
- Engine degreasing
- Industrial equipment
- Machinery



Nonfood Compounds
Program Listed A1
Registration #154405

PACKAGING

M-02809	1 Qt. (12/Case)
M-02801	1 Gal (4/Case)
M-02805	5 Gal
M-02807	55 Gal
M-02803	275 Gal

PRODUCT DESCRIPTION

ENVIROGREEN EXTREME SG is a multi-purpose, heavy duty, natural bio-based solvent degreaser. It is biodegradable and non-toxic. Removes heavy grease, oils and dirt quickly and safely. Use to degrease and clean automotive parts, oilfield equipment, machined parts, industrial machinery and other difficult-to-clean surfaces.

Replaces and outperforms d'limonene degreasers and petroleum solvents such as mineral spirits and naphtha.

This product is registered with the NSF as a K1 cleaner and degreaser for use in food processing facilities.

APPLICATIONS

PARTS WASHING SOLVENT:

Excellent for replacing petroleum solvents in parts washing equipment. Safe, non-flammable alternative to mineral spirits and other petroleum products. Removes lubricants and cutting oils from machined parts. Provides short-term corrosion protection to prevent flash rust on parts. Use on Ferrous and Non-Ferrous Metals. Safe on most plastics.

- Machined parts
- Engines
- Transmissions
- Rear ends

HEAVY DUTY DEGREASING:

Removes all grease and oil from metal surfaces. Removes petroleum based oils as well as animal fats and vegetable based oils.

- Grease
- Motor oil
- Lubricants
- Carbon deposits
- Cutting fluids
- Animal fats
- Vegetable oils
- Machine shops
- Industrial plants
- Commercial facilities

Continued on next page



ENVIROGREEN EXTREME SG

BIODEGRADABLE INDUSTRIAL CLEANER DEGREASER SOLVENT

TYPICAL ANALYSIS

VOC (ASTM E-1868) g/L:.....7.1
 % VOC BY WEIGHT.....0.8%
 VAPOR PRESSURE (mmHg @ 68°F).....< 0.04
 EVAPORATION RATE:< 0.01
 KB VALUE:61 (d'Limonene KB: 56, Mineral Spirits KB: 35)
 SPECIFIC GRAVITY: 0.882 g/mL @ 25°C
 APPEARANCE/ODOR:..... Light Yellow Liquid/Slight Odor
 DIELECTRIC STRENGTH: 42.2 KV
 BOILING POINT: > 200°C
 VAPOR PRESSURE:< 1.0 mm Hg @ 68°F
 HIGH FLASH POINT: > 300° F (TCC Method)
 READILY BIODEGRADABLE: 95% degraded in soil in 28 days
 SARA TITLE III 313:..... Not Reportable
 TSCA (Toxic Substance Control Act):..... Listed in Inventory

HMIS		NFPA	
HEALTH	FLAMMABILITY	Health Hazard	Instability
0	1	0	1
0	0	0	0
PERSONAL PROTECTION			

COMPARISONS WITH COMMON SOLVENTS

Solvent	Flash Point (°F) Closed Cup	Boiling Point @ 760 mm Hg	Evaporation Rate @ 25°C (NBAC=1.00)	Specific Gravity g/mL @ 25°C	Viscosity cP @ 25°C
EnviroGreen EXT SG	> 300	> 600	< 0.01	0.882	4.50
Mineral Spirits	107	160 - 187	0.16	0.775	0.88
VM&P Naphtha	58	124 - 142	1.81	0.748	0.62
Toluene	40	110.6	2.00	0.863	0.57
d'Limonene	121	175 - 176	0.005	0.843	3.50

DIRECTIONS

This product is used straight and can be applied by dipping, brushing, or spraying. Its high flash point makes it safe for industrial applications. May be safely heated to 140°F.