

Safety Data Sheet

Issue Date: 02-Nov-2017 Revision Date: Version

1. IDENTIFICATION

Product Identifier

Product Name STAMPING OIL VXT

Other means of identification

SDS#

Item# E-2420-05, E-2420-55, E-2420-275

Recommended use of the chemical and restrictions on use

Recommended Use Metalworking fluid

Details of the supplier of the safety data sheet

Supplier Address

Ashburn Chemical Technologies

7403 Wright Rd Houston, TX 77041

Emergency Telephone Number

Company Phone Number Emergency Telephone (24 hr) 832-399-1000

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Transparent Physical State Liquid Odor Mild petroleum

yellow /light amber

Classification

Aspiration Hazard Category 1

Signal Word DANGER

Hazard Statements

May be fatal if swallowed and enters airways.



<u>Precautionary Statements - Prevention</u>

Avoid breathing dust/fume/gas/mist/vapors/spray

<u>Precautionary Statements – Response</u>

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Revision Date: STAMPING OIL VXT

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Mineral Oil, Hydrotreated Light Naphthanic	64742-52-5	80-90

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper evelids.

Consult a physician.

Skin Contact Wash contact areas with soap and water. Remove contaminated clothing and lauder before

reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation Remove from further exposure and keep person at rest in a position comfortable for

breathing. Get medical advice/attention if you feel unwell or are concerned.

Ingestion Do not induce vomiting without medical advice. Seek immediate medical attention/advice.

Most important symptoms and effects

Symptoms Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest

May cause irritation to the mucous membranes and upper respiratory tract

See SECTION 11 for delayed and chronic effects.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which

can be fatal.

5. FIRE-FIGHTING MEASURES

Suitable / Unsuitable Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames. **Extinguishing Media**

DO NOT use stream of water (could cause fire to spread).

Specific Hazards Arising

from the Chemical

monoxide, carbon dioxide and unidentified organic compounds will be evolved when this

A mixture of airborne solids, liquids and gases including smoke, fumes, carbon,

material undergoes combustion.

Protective equipment /

(approved or equivalent) and full protective gear. **Precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin or eyes.

Avoid breathing dust/fume/gas/mist/vapors/spray See SECTION 8 for Personal Protective Equipment

Environmental Precautions Prevent entry into waterways, rivers, lakes, drains, surface water, or ground water.

Prevent further leakage or spillage if safe to do so.

See SECTION 12 for Ecological Information

STAMPING OIL VXT Revision Date:

OFAMILING CIE VA

Methods for Clean-UpAbsorb or cover with dry earth, sand or other non-combustible material.

Sweep up absorbed material and shovel into suitable containers for disposal. If the product contaminates rivers and lakes or drains inform respective authorities Discard any product, residue, disposable container or liner in full compliance with federal,

state, and local regulations.

See SECTION 13 for Waste Disposal

7. HANDLING AND STORAGE

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice.

Avoid breathing fumes, vapors, mists, spray.

Wash face, hands, and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

See SECTION 8 for Personal Protection. See SECTION 2 for Precaution Statements.

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place.

Do not store in open or unlabeled containers.

Store away from heat and open flame. Storage temperature 5-40°C (41-104°F)

Incompatible Materials Oxidizing agents. Strong alkalis. Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH STEL
Mineral Oil, Hydrotreated Light Naphthanic 64742-52-6	TWA: 5 mg/m ³ STEL: 10 mg/m ³	PEL: 5 mg/m ³ 8 hours (mist).	STEL: 10 mg/m ³ 15 minutes.

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists OSHA: Occupational Safety and Health Administration

NIOSH: National Institute for Occupational Safety and Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit TWA: Time Weighted Average

Appropriate engineering controls

Engineering Controls Provide exhaust ventilation or adequate ventilation is required to keep airborne

concentrations of vapors below their respective threshold limit value (TLV).

Maintain eye wash fountain and quick-drench facilities in work area.

maniani oje maon roumani ana quien aremen naomine in mem

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side shields.

Skin and Body Protection Chemical or oil resistant clothing is recommended.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. ATA

In case of inadequate ventilation wear respiratory protection

General Hygiene Considerations Avoid contact with skin, eyes and clothing.

After handling this product, wash hands before eating, drinking, or smoking.

Remove contaminated clothing and lauder before reuse

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid

Appearance Transparent Odor Mild Petroleum Odor

Revision Date: STAMPING OIL VXT

Color Yellow /light amber **Odor Threshold** Not determined

Values Remarks • Method Property

pН

Not determined **Melting Point/Freezing Point** Not determined

Boiling Point/Boiling Range 224 °C / > 435 °F **Flash Point**

146 °C / > 295 °F Cleveland Open Cup ASTM D 92

Evaporation Rate Not determined

Flammability OSHA Class III-B Combustible liquid

Upper Flammability Limits Not determined **Lower Flammability Limit** Not determined **Vapor Pressure** Not determined

Vapor Density > 5 (Air=1)

Specific Gravity 0.88-0.92 **Water Solubility** Insoluble

Solubility in other solvents Not determined

Dynamic Viscosity 75-85 SUS @ 38°C (100°F)

Partition Coefficient Not determined **Auto-ignition Temperature** > 315 °C / > 600°F

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions.

Chemical Stability Stable under recommended storage conditions.

Possibility of Hazardous Reactions Stable under recommended storage conditions.

Conditions to Avoid Incompatible Materials.

Incompatible Materials Oxidizing agents. Strong alkalis. Strong acids.

Hazardous Decomposition ProductsCarbon oxides. Irritating aldehydes and ketones when heated to combustion.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye Contact May cause temporary irritation

Skin Contact Prolonged contact may defat and dry skin but is neither an irritant nor a sensitizer.

Inhalation May be fatal if enter airways.

Ingestion May be fatal if swallowed. Do not induce vomiting, may increase risk of product aspiration

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute Effects Not applicable.

Chronic Effects Prolonged inhalation may be harmful.

Information on physical, chemical and toxicological effects

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50		
Mineral Oil, Hydrotreated Light Naphthanic 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h		

STAMPING OIL VXT Revision Date:

Aspiration hazard May be fatal if swallowed and enters airways.

CarcinogenicityThe classification as a carcinogen need not apply if it can be shown that the substance

contains less than 3 % DMSO extract as measured by IP 346.

STOT- repeated/single exposure Not classified

Gem Cell Mutagenicity No data available.

Reproductive Toxicity No data available.

Other information Risk of chemical pneumonia after aspiration into lung

12. ECOLOGICAL INFORMATION

Ecotoxicity Not expect to be harmful to aquatic organism

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Mineral Oil, Hydrotreated Light Naphthanic 64742-53-6		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50

Persistence/Degradability Not inherently biodegradable

Bioaccumulation Bioaccumulation is unlikely to be significant because of the low water solubility

Mobility Liquid under most environmental conditions. Float on water.

If enters soil it will absorb to soil particles and will not be moble

Other Adverse Effects No other adverse environmental effects (ozon depletion, photochemical ozone creation)

13. DISPOSAL CONSIDERATIONS

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated.

ATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Mineral Oil, Hydrotreated	X	Х		Х		Х	Х	Χ	X	Χ
Light Naphthanic										

Legend:

STAMPING OIL VXT Revision Date:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA This material, as supplied, does not contain any substances regulated as hazardous

substances under the Comprehensive Environmental Response Compensation and

Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and

Reauthorization Act (SARA) (40 CFR 355

SARA 311/312 Hazard Categories Petroleum distillates, hydrotreated light naphthenic 64742-52-5

Acute Health Hazard

SARA 313 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986

(SARA). This product does not contain any chemicals which are subject to the reporting

requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the

Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Mineral Oil, Hydrotreated Light	X	X	X
Naphthanic			

X: not regulated

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	Not determined

Issue Date: Nov-02-2017
Revision Date:
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet