



STAMPING OIL VXT

FEATURES & BENEFITS

- Designed for stamping and drawing
- Excellent lubricity
- Heavy-duty applications
- Non-chlorinated EP additives
- Low vapor pressure and non-objectionable odor

HEAVY DUTY STAMPING LUBRICANT

PRODUCT DESCRIPTION

STAMPING OIL VXT is a heavy-duty stamping and drawing fluid for use on ferrous and nonferrous materials. This product provides excellent lubrication. Stamping Oil VXT significantly increases tool and die life and greatly reduces wear.

Stamping Oil VXT does not contain nitrates, chlorine, sulfur, phenols, molybdenum compounds or graphite. It contains no solvent and is considered a low VOC lubricant.

APPLICATION

Use full strength. Do not dilute.

TYPICAL ANALYSIS

APPEARANCE:Amber Viscous Fluid

ACTIVE SULFUR:None

TOTAL CHLORINE:None

SILICONES:None

VISCOSITY: 80 (SUS @ 100°F)

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metalworking fluid additives.

PACKAGING

E-2420-05	5 Gallon
E-2420-55	55 Gallon
E-2420-275	275 Gallon