

# 7030WG



## Features & Benefits

- Does Not Contain Chlorine, Sulphur, or Phosphorous
- Provides Long Sump Life
- Excellent Tramp Oil Rejection
- Good Corrosion Protection
- Contains Antifoaming Agents Which Are Free-Rinsing Surfactants That Will Not Impair Subsequent Finishing

## PRODUCT DESCRIPTION

**APEX 7030WG** is a moderate duty, semi-synthetic water soluble cutting & grinding fluid. It will increase blade, tool, or wheel life & production. The raw materials are designed to resist bacteria & fungus. It provides long-term, worry-free sump life.

## TYPICAL ANALYSIS

APPEARANCE: .....Blue or Undyed (light yellow) Liquid  
 pH @ 5% SOLUTION:..... 9.4  
 SPECIFIC GRAVITY: ..... 1.02  
 ODOR:.....Mild  
 FLASH POINT: .....None

## APPLICATION

Recommended for turning, milling, drilling, sawing, and grinding on both ferrous and non-ferrous metals.

## RECOMMENDED STARTING DILUTIONS

Operation	Carbon Steels, Cast Steels	High Alloy Steels, Stainless Steels	Aircraft, Tool Steels	Copper, Aluminum
Machining-Milling Drilling, Turning	1:20 (5.0%)	1:15 (6.7%)	1:10 (10.0%)	1:20 (5.0%)
Grinding	1:20 (5.0%)	1:20 (5.0%)	1:20 (5.0%)	1:20 (5.0%)
Reaming, Tapping, Sawing, Broaching	1:15 (6.7%)	1:10 (10.0%)	1:10 (10.0%)	1:15 (6.7%)

## REFRACTOMETER READINGS

Dilution Ratio	1:10 (10.0%)	1:15 (6.7%)	1:20 (5.0%)	1:25 (4.0%)	1:30 (3.3%)
Refractometer Reading	3.1	2.1	1.6	1.4	1.2

## PACKAGING

Blue  
 A-7030-05 5 Gal Pail  
 A-7030-55 55 Gal Drum  
 A-7030-275 275 Gal Tote

Undyed  
 A-7031-05 5 Gal Pail  
 A-7031-55 55 Gal Drum  
 A-7031-275 275 Gal Tote

## NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.



7403 Wright Rd. Houston, TX 77041  
 ph: 832.399.1000 fax: 832.399.1010  
 www.ashburnchemical.com

