

7030



Features & Benefits

- Does Not Contain Chlorine, Sulphur, or Phosphorous
- Contains Antifoaming Agents Which Are Free-Rinsing surfactants That Will Not Impair Subsequent Finishing
- Provides Long Sump Life
- Excellent Corrosion Protection
- Excellent Tramp Oil Rejection
- Mild Pleasant Odor
- Good Corrosion Protection

PRODUCT DESCRIPTION

APEX 7030 is a moderate duty, semi-synthetic, water soluble, cutting and grinding fluid. It will increase blade, tool or wheel life and production. The raw materials are designed to resist bacteria and fungus. It provides long-term, worry-free sump life.

TYPICAL ANALYSIS

APPEARANCE: Blue
 pH @ 5% SOLUTION: 9.4
 SPECIFIC GRAVITY: 1.01
 ODOR: Mild
 FLASH POINT: None

APPLICATION

Recommended for turning, milling, drilling, sawing, and grinding on both ferrous and non-ferrous metals.

RECOMMENDED STARTING DILUTIONS

Operation	Carbon Steels, Cast Steels	High Alloy Steels, Stainless Steels	Aircraft, Tool Steels	Copper, Aluminum
Machining-Milling Drilling, Turning	1:20 (5.0%)	1:15 (6.7%)	1:10 (10.0%)	1:20 (5.0%)
Grinding	1:20 (5.0%)	1:20 (5.0%)	1:20 (5.0%)	1:20 (5.0%)
Reaming, Tapping, Sawing, Broaching	1:15 (6.7%)	1:10 (10.0%)	1:10 (10.0%)	1:15 (6.7%)

REFRACTOMETER READINGS

Dilution Ratio	1:10 (10.0%)	1:15 (6.7%)	1:20 (5.0%)	1:25 (4.0%)	1:30 (3.3%)
Refractometer Reading	4.8	3.3	2.3	1.9	1.6

PACKAGING

A-7535-05 5 Gal Pail
 A-7535-55 55 Gal Drum
 A-7535-275 275 Gal Tote

Undyed
 A-7536-05 5 Gal Pail
 A-7536-55 55 Gal Drum

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metal working fluid additives.



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com

