

Ashburn 2900 RI

Features & Benefits

- Water Soluble
- Multi-Purpose
- Excellent Rust Prevention
- Soft Residue

Rust Inhibitor

PRODUCT DESCRIPTION

Ashburn 2900 RI is a multi-purpose, synthetic, water-soluble rust and corrosion preventative designed for in-process protection of ferrous materials. This product will provide up to 9 months of indoor rust protection. Parts protected with **2900 RI** can be welded or painted over.

Ashburn 2900 RI can also be used as a parts cleaner to remove dirt, grime and oil from metal surfaces while providing corrosion protection.

TYPICAL ANALYSIS

WEIGHT:.....8.48 LB/GL
 SPECIFIC GRAVITY:..... 1.016
 PH@5%CPNC.:9.00
 FLASH POINT: >300°F (TCC Method)
 RESIDUE:.....Soft Film
 APPEARANCE:..... Clear Amber Fluid

APPLICATION

The 2900 RI can be applied by dipping, spraying, or flooding. Dilute the product 10:1 with water for heavy-duty applications, 15:1 - 25:1 for moderate applications, and 30:1 - 50:1 for light duty applications.

PACKAGING

E-2905-05 5 Gallon (4/Case)
 E-2905-55 55 Gal Pail
 E-2905-275 275 Gal Drum



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com