

Ashburn 3200 RI

Rust Inhibitor

PRODUCT DESCRIPTION

Ashburn 3200 RI is a heavy-duty, multi-purpose, synthetic, water-soluble rust and corrosion preventative designed for in-process protection of ferrous and nonferrous materials. This product will provide up to 9 months of indoor rust protection. Leaves a soft, non-tacky residue.

Ashburn 3200 RI can be used in circulating coolant systems to prevent rust from occurring on machine tool surfaces and machined parts.

TYPICAL ANALYSIS

Form	Liquid
Color	Clear Yellow
Odor	Mild Glycol
Residue	Fluid
Specific Gravity.....	1.08
pH @ 5% Conc.....	8.2

DILUTION RATIO

In Coolant System

Dilute with 20 parts of water to 1 part of 3200 RI.
Adjust to reach desired objectives.

For Rust Protection and Parts Washing Systems

The 3200 RI can be applied by dipping, spraying, or flooding.
Use straight or dilute the product 10:1 with water for heavy-duty applications, 15:1 - 25:1 for moderate applications, and 30:1 - 50:1 for light duty applications

For Tank Side Addition to Improve Rust Protection

Start with 1-2 gallons of 3200 RI per 100 gallons in tank.
(This will give you a 1.0% - 2.0% addition). Repeat as needed.

PACKAGING

B-3200-14	1 Gallon (4/Case)
B-3200-05	5 Gallon
B-3200-55	55 Gallon



7403 Wright Rd. Houston, TX 77041
ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com