



# VANISHING OIL ML

## FEATURES & BENEFITS

- No oily residue
- Non-reactive to metals
- Ideal for drawing and stamping (light gauge material)
- Works on ferrous and nonferrous metals
- Excellent lubrication

## PRODUCT DESCRIPTION

**VANISHING OIL ML** is a very low viscosity oil which is fortified with mild extreme pressure additives. It will evaporate at room temperature in a few hours after use. This product leaves an excellent finish on cut, drawn or stamped parts.

## APPLICATION

Ashburn Vanishing Oil ML is ready to use, do not dilute.

## TYPICAL ANALYSIS

APPEARANCE:.....Clear Oil  
 DENSITY: ..... 7.4 LB/GL  
 FLASH POINT:.....> 266°F (PMCC METHOD)  
 SOLUBILITY IN WATER:..... Nil  
 VISCOSITY: .....43 SSU @ 100°F  
 SULFUR: .....NONE  
 CHLORINE: ..... <5.00%  
 PHOSPHOROUS: .....NONE

## NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metalworking fluid additives.

## PACKAGING

E-7521-14	1 Gallon (4/case)
E-7522-05	5 Gallon
E-7523-55	55 Gallon
E-7523-275	275 Gallon